



2255 AGATE CT. SIMI VALLEY CA. 93065
Tel: (805) 581-0333 / Fax: (805) 584-1913



“Keeping You Cool Under Pressure”

Installation Instruction for '01- Subaru WRX High Performance Intercooler System (Part No. 2-450)

TOOLS REQUIRED:

- 1.) Standard mechanic hand tools
- 2.) Wrenches (Metric)
- 3.) Sockets and Ratchets (Metric)

INSTALLATION:

- 1.) Disconnect the air by-pass valve hoses from the intercooler.
- 2.) Unbolt both bolts that secure the air by pass valve to the intercooler.
- 3.) Remove both bolts that secure the intercooler to the mounting brackets.
- 4.) Loosen the hose clamp that connects the intercooler air duct to the turbocharger and separate.
- 5.) Loosen the hose clamp that connects the intercooler to the throttle body and separate.
- 6.) Loosen the hose clamps and remove the intercooler hose duct.
- 7.) Unbolt and remove the intercooler ducts from the intercooler and re-install onto the new intercooler tightening the bolt to 16N-m (1.6 kgf-m, 11.7 ft-lb)
- 8.) Re-install the intercooler tightening the bolts to 16 N-m (1.6kgf-m, 1.7 ft-lb).